



SELIG INDUSTRIES
 Acuity Specialty Products Group, Inc.
 P.O. BOX 43106
 ATLANTA, GA 30336
 TECH SERVICE 1 (800) 832-4724
 www.seligind.com

Material Safety Data Sheet

and Safe Handling and Disposal Information

Section 1. Chemical Product and Company Identification

Product name Selig Chain & Cable HP Lubricant
Product Use Aerosol Multi-purpose Lubricant
Product Code L897
Date of issue 03/22/07 **Supersedes**

Emergency Telephone Numbers For MSDS Information:
 Selig Industries
 Technical Services (800) 832-4724

For a Medical Emergency:
 INFOTRAC
 (877) 541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency:
 CHEMTREC
 (800) 424-9300 - All Calls Recorded
 In District of Columbia: (202) 483-7616

Prepared by Compliance Services Group
 Acuity Specialty Products Group
 1420 Seaboard Industrial Blvd.
 Atlanta, GA 30318

396



TONY ANGELO CEMENT CO
 46850 GRAND RIVER AVE
 NOVI MI 48374-1327

Printing date: 05/20/10

Section 2. Composition, Information on Ingredients

Name of Hazardous Ingredients	CAS #	% by Weight	Exposure Limits
Paraffinic distillate, hydrotreated heavy	64742-54-7	80 - 90	ACGIH TLV (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Mist OSHA PEL (United States). TWA: 5 mg/m ³ 8 hour(s).
PROPANE; dimethylmethane propyl hydride	74-98-6	10 - 20	OSHA PEL (United States). TWA: 1000 ppm 8 hour(s).

Section 3. Hazards Identification

Acute Effects **Routes of Entry** Dermal contact. Eye contact. Inhalation.

Skin May cause skin irritation. Skin inflammation is characterized by itching, scaling, or reddening.

Eyes Causes eye irritation. Inflammation of the eye is characterized by redness, watering, and itching.

Inhalation May cause respiratory tract irritation. Can cause central nervous system depression. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Medical Conditions Aggravated by Overexposure: Respiratory

HMIS	
Health	1
Fire Hazard	3
Reactivity	0
Personal Protection	B

Ingestion Harmful if swallowed. Aspiration hazard if swallowed- can enter lungs and cause damage.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse health effects are lessened by following all prescribed safety precautions, including use of proper personal protective equipment.

Carcinogenic Effects Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Chronic Effects Inhalation of spray mists or vapors may cause central nervous system depression characterized by headache, dizziness, nausea, and/or stupor. Prolonged or repeated contact may dry skin and cause irritation. Medical Conditions Aggravated by Overexposure: Skin, Eyes and Respiratory.

See Toxicological Information (section 11)

Section 4. First Aid Measures

Eye Contact Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention.

Skin Contact Wash affected area with soap or mild detergent and water. Get medical attention if irritation develops.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion Aspiration hazard if swallowed- can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flash Point Not available. Flammable Limits Not available.

Flammability FLAMMABLE. (CSMA)

Fire Hazard FLAMMABLE LIQUID AND VAPOR. Vapor may cause flash fire. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions or when heated.

Fire-Fighting Procedures Use dry chemical or CO₂. Cool closed containers exposed to fire with water. Wear special protective clothing and positive pressure, self-contained breathing apparatus.

**Section 6. Accidental Release Measures**

Spill Clean up Large spills are unlikely due to packaging.

Section 7. Handling and Storage


Handling CONTENTS UNDER PRESSURE. Keep away from heat, sparks and flame. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or spray mists. Use with adequate ventilation. Wash contaminated clothing before reusing.

Storage Keep container tightly closed. Keep container in a cool, well-ventilated area. Do not store above 49°C (120.2°F). Do not puncture or incinerate. Keep out of the reach of children.

Section 8. Exposure Controls, Personal Protection

Personal Protection

Protective Clothing (Pictograms)

Eyes Safety glasses. 

Body For prolonged or repeated handling, use gloves.. Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves.

Respiratory Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate.

Section 9. Physical and Chemical Properties

Physical State Liquid. (Aerosol.) Color Amber.

pH Not applicable. Odor Sweetish. Solvent-like.

Boiling Point Decomposes. Vapor Pressure Not determined.

Specific Gravity 0.86 (Water = 1) Vapor Density Not determined.

Solubility Insoluble in cold water, hot water. Evaporation Rate Not available.

VOC (Consumer) 123.63 (g/l). 1.03 lb/gal 14.4%

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Incompatibility Avoid contact with strong oxidizers, excessive heat, sparks or open flame.

Hazardous Polymerization Will not occur.

Hazardous Decomposition Products Carbon Dioxide, Carbon Monoxide and other organic materials..

Section 11. Toxicological Information

Toxicity to Animals Not available.

Section 12. Ecological Information

Ecotoxicity Not available

Biodegradable/OECD Not available.

Section 13. Disposal Considerations

Waste Waste must be disposed of in accordance with federal, state and local environmental control regulations. Waste Stream Code: D001

Information Classification: Hazardous Waste

Consult your local or regional authorities.

Section 14. Transport Information

Proper shipping name Consumer Commodity

DOT Classification ORM-D UN number Not available.

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

Willow Seedling
1105517-9232
- 303-